




Outside serrated cable ties with low profile head and manufactured with UV-resistant polymer.



Tool-free installation



Technical Data

CODE	type	NOMINAL DIMENSIONS						BUNDLE DIAMETER	
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
Black		A	B	C	E	F	G	ø min	ø max
6551	A	180	8,8	1,7	14,7	25	6,7	10	38
6553	B	270	8,8	1,8	14,7	34	6,6	25	63
6555	B	360	8,8	1,8	14,7	34	6,6	25	93

COLORS

■ Black

MATERIALS

Material: techno-polymer black UV stabilized and weather resistant

Halogen free

Material flammability rating:

UL 94-HB

Excellent resistance to: aromatic solvents, oils, greases and derivatives

Good resistance to: bases

Limited resistance to: acids

Not resistant to:

phenols and to chlorinated solvents

APPLICATION

Installation temperature:

-30°C ÷ 60°C

Working temperature:

-40°C ÷ 85°C

APPROVALS / CERTIFICATIONS

EC Directives:

The materials used to produce the cable ties comply with EC Directives:

- 1907/2006/CE (REACH)

Product conformity:

The products are tested in accordance with CEI EN 62275 «Cable management systems - Cable ties for electrical installations».

The UV resistance of the products was tested according to ISO 4892-2 «Plastics - Methods of exposure to laboratory light sources - Part 2: Xenon-arc lamps».

Mechanical features and packaging

CODE	MECHANICAL FEATURES Newton (N) Tensile strength**	PACKAGING	
		(pcs) Bag	(pcs) Box
6551	390	100	4.000
6553	560	100	2.500
6555	560	100	2.000

** Please consider a suitable safety factor equal or above 2